

Printing date 24.08.2023

Version number 4 (replaces version 3) Revision: 24.08.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Trade name weber 3400 Finishing screed

Safety data sheet no.: 358P0547

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Construction chemicals Filler and surfacer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

1.4 Emergency telephone number:

0800 147 111 (toll-free) 09 471 977 (standard rate) Finnish Poison Information Centre

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05

Signal word Danger

Hazard-determining components of labelling:

cement portland, grey

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements

P102 Keep out of reach of children.

P261 Avoid breathing dust.

(Contd. on page 2)



Printing date 24.08.2023 Version number 4 (replaces version 3) Revision: 24.08.2023

Trade name weber 3400 Finishing screed

(Contd. of page 1)

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

Results of PBT and vPvB assessment PBT: Does not contain PBT substances. vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Ready-mixed mortar with Portland cement

Dangerous components:			
CAS: 1317-65-3 EINECS: 215-279-6	calcium carbonate substance with a Community workplace exposure limit	50-75%	
CAS: 7778-18-9 EINECS: 231-900-3 Reg.nr.: 01-2119444918-26-xxxx	calcium sulphate, natural substance with a Community workplace exposure limit	5-10%	
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	2-5%	

SVHC Void

Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Supply fresh air and to be sure call for a doctor.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eve contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

(Contd. on page 3)



Printing date 24.08.2023 Version number 4 (replaces version 3)

Trade name weber 3400 Finishing screed

(Contd. of page 2)

Revision: 24.08.2023

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray

or alcohol resistant foam.

The product is not combustible.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Wear protective clothing.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Store in dry conditions.

7.3 Specific end use(s) No further relevant information available.

EUG



Printing date 24.08.2023 Version number 4 (replaces version 3) Revision: 24.08.2023

Trade name weber 3400 Finishing screed

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

Finland: cement dust

HTP(8h) = 5 mg/m3, inhalable dust HTP(8h) = 1 mg/m3, respirable dust

DNELs	DNELs				
CAS: 6599	CAS: 65997-16-2 Cement, alumina, chemicals				
Inhalative	Derived No Effect Level	2.5 mg/m³ (worker systemic long term value)			
		5 mg/m³ (worker systemic short term value)			
CAS: 7778	8-18-9 calcium sulphate	, natural			
Oral	Derived No Effect Level	1.52 mg/kgxday (consumer systemic long term value)			
		11.4 mg/kgxday (consumer systemic short term value)			
Inhalative	Derived No Effect Level	21.17 mg/m³ (worker systemic long term value)			
		5,082 mg/m³ (worker systemic short term value)			
		5.29 mg/m³ (consumer systemic long term value)			
		3,811 mg/m³ (consumer systemic short term value)			

	3,811 mg/m² (consumer systemic short term value)		
CAS No. / De	signation of material / % / Type / Value / Unit		
CAS: 1317-65-3 calcium carbonate			
TWA (Italy)	Long-term value: 10 mg/m³ (e)		
CAS: 7778-18-9	calcium sulphate, natural		
AGW (Germany)	Long-term value: 6 A mg/m³ DFG		
LEP (Spain)	Long-term value: 10 mg/m³ e		
TWA (Italy)	Long-term value: 10 mg/m³ (i)		
VLE (Portugal)	Long-term value: 10 mg/m³ Fração inalável; Sintomas nasais		
CAS: 65997-15-1	cement portland, grey		
AGW (Germany)	Long-term value: 5 E mg/m³ DFG		
LEP (Spain)	Long-term value: 4 mg/m³ fracción respirable: e, d		
TWA (Italy)	Long-term value: 1 mg/m³ (e, j), A4		
VLE (Portugal)	Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma		
HTP (Finland)	Long-term value: 5* 1** mg/m³ *hengittyvä pöly, **alveolijae		
	(Contd. on page 5)		



Printing date 24.08.2023 Version number 4 (replaces version 3) Revision: 24.08.2023

Trade name weber 3400 Finishing screed

(Contd. of page 4)

8.2 Exposure controls

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Use suitable respiratory protective device when high

concentrations are present.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Filter P2.

Hand protection

The hands must be cleaned from the powder before putting on the gloves.

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Check protective gloves prior to each use for their proper condition.

Eye/face protection Tightly sealed goggles **Body protection**: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour: Grey

Odour: Specific type Odour threshold: Not determined.

Boiling point or initial boiling point and boiling

range Undetermined.

Flammability Product is not flammable.

Lower and upper explosion limit

Lower:
Upper:
Not determined.
Not applicable
Auto-ignition temperature:
Not determined.
Not determined.
Not determined.
Not determined.

pH at 20 °C <11

Viscosity:

Kinematic viscosity

dynamic:

Not determined.

Not determined.

Solubility

Water: Miscible

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure:

Not applicable.

(Contd. on page 6)





Printing date 24.08.2023 Version number 4 (replaces version 3) Revision: 24.08.2023

Trade name weber 3400 Finishing screed

(Contd. of page 5)

Density and/or relative density

Density at 20 °C: 1.4-1.6 g/cm³ **Vapour density** Not applicable.

Particle characteristics

See section 3.

9.2 Other informationNo further relevant information available.

Appearance:

Form: Powder

Important information on protection of health

and environment, and on safety.

Explosive properties: Product does not present an explosion hazard.

Minimum ignition energy

Solvent content:

Organic solvents: 0.0 % EU-VOC (%) 0.00 % EU-VOC (g/L)

Solids content: 100 %

Change in condition Softening point/range

Organic peroxides

Corrosive to metals

Desensitised explosives

Oxidising properties Not determined. Evaporation rate Not applicable.

Information with regard to physical hazard

classes

Explosives Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void **Pyrophoric solids** Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void Oxidising solids Void

SECTION 10: Stability and reactivity

10.1 Reactivity When mixed with water the product hardens forming a stable non-reactive mass.

Void

Void

Void

- 10.2 Chemical stability Stable at recommended storage conditions
- 10.3 Possibility of hazardous reactions No dangerous reactions known

(Contd. on page 7)



Printing date 24.08.2023 Version number 4 (replaces version 3) Revision: 24.08.2023

Trade name weber 3400 Finishing screed

10.4 Conditions to avoid

(Contd. of page 6)

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

10.5 Incompatible materials: Acids, ammonium salts, aluminum, non-precious metals.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compo	nents	1	Туре	1	Value	1	Species	
CAS: 13	317-65	-3 calcium (carbonate					
Oral	LD50	>5,000 mg/	kg (Rat)					
CAS: 6	5997-1	6-2 Cement	, alumina,	chei	micals			
Oral	LD50	>2,000 mg/	kg (Rat)					
Dermal	LD50	>2,000 mg/	kg (Rat)					
CAS: 77	778-18	-9 calcium s	sulphate, r	natur	al			
Oral	LD50	>2,000 mg/	kg (Rat)					
CAS: 6	CAS: 65997-15-1 cement portland, grey							
Dermal	LD50	>2,000 mg/	kg (Rabbit)					

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

rigidatio toxiony. Not sideomed de naminar le aqualle me				
	Type of te	st / Effective concentration / Method / Assessment		
CAS: 1317-65-3 calcium carbonate				
	LC50/96h	>10,000 mg/l (Oncorhynchus mykiss (Rainbow trout))		
	EC50/48h	>1,000 mg/l (Daphnia magna)		
	EC50/72h	>200 mg/l (Algae)		

(Contd. on page 8)



Printing date 24.08.2023 Version number 4 (replaces version 3) Revision: 24.08.2023

Trade name weber 3400 Finishing screed

	(Contd. of page 7)			
CAS: 6599	CAS: 65997-16-2 Cement, alumina, chemicals			
LC50/96h	100 mg/l (Fish)			
EC50/48h	5.4 mg/l (Daphnia magna)			
EC50/72h	3.6 mg/l (Algae)			
CAS: 7778	3-18-9 calcium sulphate, natural			
LC50/48h	79-1,970 mg/l (Daphnia magna)			
LC50/96h	79-2,980 mg/l (Fish)			
EC50/72h	>79 mg/l (Selenastrum capricornutum (Green algae))			

- **12.2 Persistence and degradability** The product is not biodegradable.
- 12.3 Bioaccumulative potential Does not accumulate in organisms
- **12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

Remark

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment		
CAS: 65997-16-2 Cement, alumina, chemicals		
EC 50 (3h) 1,000 mg/l (Activated sludge)		
CAS: 7778-18-9 calcium sulphate, natural		
EC 50 (3h) >1,000 mg/l (Activated sludge)		

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

Waste disposal key:

The classification in a waste code according to the european waste catalogue (EWC) is to be made in accordance with the regional responsable for waste disposal

	European waste catalogue				
17 01 01 concrete					
	16 03 03* inorganic wastes containing hazardous substances				
		wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10			

(Contd. on page 9)



Printing date 24.08.2023 Version number 4 (replaces version 3) Revision: 24.08.2023

Trade name weber 3400 Finishing screed

(Contd. of page 8)

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Thoroughly shake out sacks.

SECTION 14: Transport informat	
14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments Not applicable.	
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Cement clinker is exempted from REACH registration (REACH Article 2(7)(b) and Annex V point 10)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII Entry no. 47 Chromium VI compounds)

Conditions of restriction: 47

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 10)



Printing date 24.08.2023 Version number 4 (replaces version 3) Revision: 24.08.2023

Trade name weber 3400 Finishing screed

REGULATION (EU) 2019/1148

(Contd. of page 9)

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008		
Skin corrosion/irritation	Expert judgement	
	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

Department issuing SDS:

Saint-Gobain Finland Oy / Weber

QEHS

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

Contact:

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 520

Version number of previous version: 3

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 11)



(Contd. of page 10)



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 24.08.2023 Version number 4 (replaces version 3) Revision: 24.08.2023

Trade name weber 3400 Finishing screed

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.