

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 01.12.2022

Version number 5 (replaces version 4)

Revision: 01.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **weber 412 Coarse Render**

Safety data sheet no.: 358P0215

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

1.4 Emergency telephone number:

0800 147 111 (toll-free)

09 471 977 (standard rate)

Finnish Poison Information Centre

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05

Signal word Danger

Hazard-determining components of labelling:

cement portland, grey

calcium dihydroxide

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements

P102 Keep out of reach of children.

P261 Avoid breathing dust.

P280 Wear protective gloves / eye protection / face protection.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2022

Version number 5 (replaces version 4)

Revision: 01.12.2022

Trade name weber 412 Coarse Render

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Ready-mixed mortar with Portland cement

Dangerous components:

CAS: 1317-65-3 EINECS: 215-279-6	calcium carbonate substance with a Community workplace exposure limit	50-75%
CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	10-20%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	5-10%
CAS: 1305-62-0 EINECS: 215-137-3 Reg.nr.: 01-2119475151-45-xxxx	calcium dihydroxide ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335	≥5-<10%

SVHC Void

Additional information

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Supply fresh air and to be sure call for a doctor.

After skin contact Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2022

Version number 5 (replaces version 4)

Revision: 01.12.2022

Trade name weber 412 Coarse Render

(Contd. of page 2)

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media**Suitable extinguishing agents**

The product is not combustible.

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

6.2 Environmental precautions: No special measures required.

6.3 Methods and material for containment and cleaning up:

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities**Storage****Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Store in dry conditions.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2022

Version number 5 (replaces version 4)

Revision: 01.12.2022

Trade name weber 412 Coarse Render

(Contd. of page 3)

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs

CAS: 1305-62-0 calcium dihydroxide

Inhalative	Derived No Effect Level	Value
		4 mg/m ³ (worker local short term value)
		1 mg/m ³ (worker local long term value)
		1 mg/m ³ (consumer local long term value)
		4 mg/m ³ (consumer local short term value)

PNECs

CAS: 1305-62-0 calcium dihydroxide

Predicted No-Effect Concentration	Value
	9.32 mg/l (sea water rating factor)
	0.49 mg/l (fresh water rating factor)

CAS No. / Designation of material / % / Type / Value / Unit

CAS: 1317-65-3 calcium carbonate

Designation	Value / Unit
TWA (Italy)	Long-term value: 10 mg/m ³ (e)

CAS: 14808-60-7 Silicon dioxide (Quartz sand)

Designation	Value / Unit
BOELV (European Union)	Long-term value: 0.1* mg/m ³ *respirable fraction
MAK (Germany)	Long-term value: 0.05 mg/m ³ alveolengängige Fraktion
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m ³ Long-term value: 0.3* 0.1** mg/m ³ *total; **total, respirabel, EK
LEP (Spain)	Long-term value: 0.05 mg/m ³ *Fracción resp:n,d,y
TWA (Italy)	Long-term value: 0.025 mg/m ³ A2, (j)
VLE (Portugal)	Long-term value: 0.025 mg/m ³ Resp.;A2; fibrose pulmonar; cancro do pulmão
OEL (Sweden)	Long-term value: 0.1 mg/m ³ C, M, respirabel fraktion
HTP (Finland)	Long-term value: 0.05 0.1* mg/m ³ alveolijae;*sitovat raja-arvot, pöly

CAS: 65997-15-1 cement portland, grey

Designation	Value / Unit
AGW (Germany)	Long-term value: 5 E mg/m ³ DFG
LEP (Spain)	Long-term value: 4 mg/m ³ fracción respirable: e, d

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2022

Version number 5 (replaces version 4)

Revision: 01.12.2022

Trade name weber 412 Coarse Render

(Contd. of page 4)

TWA (Italy)	Long-term value: 1 mg/m ³ (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m ³ Fração resp.;A4,função pulm.,sintomas resp.,asma
HTP (Finland)	Long-term value: 5* 1** mg/m ³ *hengittyvä pöly, **alveolijae
CAS: 1305-62-0 calcium dihydroxide	
IOELV (European Union)	Short-term value: 4 mg/m ³ Long-term value: 1 mg/m ³ Respirable fraction
AGW (Germany)	Long-term value: 1E mg/m ³ 2(l);Y, EU, DFG
GV (Denmark)	Short-term value: 10 4* mg/m ³ Long-term value: 5 1* mg/m ³ E; *respirabel fraktion
LEP (Spain)	Long-term value: 4 mg/m ³ , 1 ppm fracción resp., VLI, d
TWA (Italy)	Long-term value: 5 mg/m ³
VL (Italy)	Short-term value: 4* mg/m ³ Long-term value: 1* mg/m ³ *frazione toracica
VLE (Portugal)	Long-term value: 5 mg/m ³ Irritação ocular, do TRS, cutânea
OEL (Sweden)	Short-term value: 4 mg/m ³ Long-term value: 1 mg/m ³
HTP (Finland)	Short-term value: 4 mg/m ³ Long-term value: 1 mg/m ³

8.2 Exposure controls

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Filter P3.

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Eye/face protection Tightly sealed goggles

Body protection: Protective work clothing.

EUG

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 01.12.2022

Version number 5 (replaces version 4)

Revision: 01.12.2022

Trade name weber 412 Coarse Render

(Contd. of page 5)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour:	Grey
Odour:	Specific type
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	Undetermined.
Flammability	Product is not flammable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable
Ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH	12-13 In water
Viscosity:	
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
Water:	Insoluble
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not applicable.
Density and/or relative density	
Density:	1.3-1.5 g/cm ³
Vapour density	Not applicable.
Particle characteristics	See item 3.

9.2 Other information

Appearance:	No further relevant information available.
Form:	Powder
Important information on protection of health and environment, and on safety.	
Auto-ignition temperature:	Product is not self-igniting.
Explosive properties:	Product does not present an explosion hazard.
Minimum ignition energy	
Solvent content:	
Organic solvents:	0.0 %
EU-VOC (%)	0.00 %
EU-VOC (g/L)	
Solids content:	100.0 %
Change in condition	
Softening point/range	
Oxidising properties	Not determined.
Evaporation rate	Not applicable.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2022

Version number 5 (replaces version 4)

Revision: 01.12.2022

Trade name weber 412 Coarse Render

(Contd. of page 6)

Information with regard to physical hazard

classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity When mixed with water the product hardens forming a stable non-reactive mass.

10.2 Chemical stability Stable at recommended storage conditions

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

10.5 Incompatible materials: Acids, ammonium salts, aluminum, non-precious metals.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 1317-65-3 calcium carbonate			
Oral	LD50	>5,000 mg/kg	(Rat)
CAS: 65997-15-1 cement portland, grey			
Dermal	LD50	>2,000 mg/kg	(Rabbit)
CAS: 1305-62-0 calcium dihydroxide			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,500 mg/kg	(Rabbit)

Skin corrosion/irritation

Causes skin irritation.

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2022

Version number 5 (replaces version 4)

Revision: 01.12.2022

Trade name weber 412 Coarse Render

(Contd. of page 7)

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards
Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity
Aquatic toxicity: Not classified as harmful to aquatic life

Type of test / Effective concentration / Method / Assessment
CAS: 1317-65-3 calcium carbonate

LC50/96h	>10,000 mg/l (Oncorhynchus mykiss (Rainbow trout))
EC50/48h	>1,000 mg/l (Daphnia magna)
EC50/72h	>200 mg/l (Algae)

CAS: 1305-62-0 calcium dihydroxide

LC50/96h	158 mg/l (Daphnia magna)
	>50.6 mg/l (Fish)
EC50/48h	49.1 mg/l (Daphnia magna)
EC50/72h	184.57 mg/l (Algae)
NOEC (14d)	32 mg/l (Daphnia magna)

12.2 Persistence and degradability The product is not biodegradable.

12.3 Bioaccumulative potential Does not accumulate in organisms

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Behaviour in sewage processing plants:
Type of test / Effective concentration / Method / Assessment
CAS: 1305-62-0 calcium dihydroxide

EC 50 (3h)	300.4 mg/l (Activated sludge)
------------	-------------------------------

(Contd. on page 9)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 01.12.2022

Version number 5 (replaces version 4)

Revision: 01.12.2022

Trade name weber 412 Coarse Render

(Contd. of page 8)

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

European waste catalogue

17 01 01	concrete
16 03 03*	inorganic wastes containing hazardous substances
10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10
HP4	Irritant - skin irritation and eye damage

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Thoroughly shake out sacks.

SECTION 14: Transport information

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

EUG

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2022

Version number 5 (replaces version 4)

Revision: 01.12.2022

Trade name weber 412 Coarse Render

(Contd. of page 9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Cement clinker is exempted from REACH registration (REACH Article 2(7)(b) and Annex V point 10)

Portland cement clinker is exempt from REACH registration (Article 2.7b and Annex V, section 10).

REACH Annex VII Restrictions: 47. Chromium VI compounds

1. Cement and cement-containing mixtures shall not be placed on the market, or used, if they contain, when hydrated, more than 2 mg/kg (0,0002 %) soluble chromium VI of the total dry weight of the cement.

2. If reducing agents are used, then without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of cement or cement-containing mixtures is visibly, legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below the limit indicated in paragraph 1.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds)

Conditions of restriction: 47

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2022

Version number 5 (replaces version 4)

Revision: 01.12.2022

Trade name weber 412 Coarse Render

(Contd. of page 10)

Relevant phrases

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/eye irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

Department issuing SDS:

Saint-Gobain Finland Oy / Weber

QEHS

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

Contact:

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 520

Version number of previous version: 4**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG