Revision: 09.09.2024



## Safety Data Sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.09.2024

Version number 4 (replaces version 3)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: weber Cultural lime cement paint, cement

Safety data sheet no.: 358P0266

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

## 1.4 Emergency telephone number:

0800 147 111 (toll-free)

09 471 977 (standard rate)

Finnish Poison Information Centre

## **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335 May cause respiratory irritation.

#### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

## **Hazard pictograms**





GHS05 GHS07

#### Signal word Danger

## Hazard-determining components of labelling:

cement, portland, white

## **Hazard statements**

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

#### **Precautionary statements**

P102 Keep out of reach of children.

(Contd. on page 2)



## according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.09.2024 Version number 4 (replaces version 3) Revision: 09.09.2024

Trade name: weber Cultural lime cement paint, cement

(Contd. of page 1)

P261 Avoid breathing dust.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### 2.3 Other hazards

**Results of PBT and vPvB assessment PBT:** Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

**Description:** Ready-mixed mortar with Portland cement

	Dangerous components:					
Γ			75-100%			
	EINECS: 266-043-4	Eye Dam. 1, H318;  Skin Irrit. 2, H315; STOT SE 3, H335 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 %				
		Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 %				
		Eye Dam. 1; H318: C ≥ 1 %				

#### **SVHC** Void

#### Additional information

The product contains white cement with a content of soluble chromium (VI) below 0.0002% (2 ppm). It doesn't need any chromate reducing agent.

For the wording of the listed hazard statements refer to section 16.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### **General information**

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation Supply fresh air and to be sure call for a doctor.

#### After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

### After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

## 4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation.

(Contd. on page 3)



## according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.09.2024 Version number 4 (replaces version 3) Revision: 09.09.2024

Trade name: weber Cultural lime cement paint, cement

(Contd. of page 2)

## 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

## Suitable extinguishing agents

Use fire extinguishing methods suitable to surrounding conditions.

The product is not combustible.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

5.3 Advice for firefighters

**Protective equipment:** Use methods suitable to surrounding conditions.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Ensure adequate ventilation.

Avoid formation of dust.

**6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.

## 6.3 Methods and material for containment and cleaning up:

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Keep receptacles tightly sealed.

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

## 7.2 Conditions for safe storage, including any incompatibilities

Storage

### Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: Store in dry conditions.

7.3 Specific end use(s) No further relevant information available.

EUG



## according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.09.2024 Version number 4 (replaces version 3) Revision: 09.09.2024

Trade name: weber Cultural lime cement paint, cement

(Contd. of page 3)

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS No. / Designation of material / % / Type / Value / Unit						
CAS: 65997-15-1 cement, portland, white						
AGW (Germany)	Long-term value: 5 E mg/m³ DFG					
LEP (Spain)	Long-term value: 4 mg/m³ fracción respirable: e, d					
TWA (Italy)	Long-term value: 1 mg/m³ (e, j), A4					
VLE (Portugal)	Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma					
HTP (Finland)	Long-term value: 5* 1** mg/m³ *hengittyvä pöly, **alveolijae					

#### 8.2 Exposure controls

## Individual protection measures, such as personal protective equipment

## General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

## Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Filter P3.

#### Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Check protective gloves prior to each use for their proper condition.

Material of gloves Nitrile impregnated cotton gloves complying with the standard EN 374-1.

## Penetration time of glove material

The exact breaktrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection** Tightly sealed goggles **Body protection**: Protective work clothing.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

**General Information** 

Colour: White Odour: Mild

Odour threshold: Not determined.

(Contd. on page 5)



## according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.09.2024 Version number 4 (replaces version 3) Revision: 09.09.2024

Trade name: weber Cultural lime cement paint, cement

(Contd. of page 4)

Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range Undetermined.

**Flammability** Product is not flammable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:Not applicableAuto-ignition temperature:Not determined.Decomposition temperature:Not determined.

**pH** 12-13

Viscosity:

**Kinematic viscosity dynamic:**Not determined.

Not determined.

Solubility

Water: Miscible

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure:

Not applicable.

Density and/or relative density

Density: Not applicable.

Bulk density at 20 °C: 1.3-1.5 g/cm3

Vapour density Not applicable.

**Particle characteristics** 

See section 3.

#### 9.2 Other information

Appearance:

Form: Powder

Important information on protection of health

and environment, and on safety.

**Ignition temperature:** Product is not self-igniting.

**Explosive properties:** Product does not present an explosion hazard.

Minimum ignition energy

Solvent content:

 Organic solvents:
 0.0 %

 EU-VOC (%)
 0.0000 %

 EU-VOC (g/L)
 0.0000 g/l

 Solids content:
 100.0 %

Change in condition Softening point/range

Oxidising properties Not determined. Evaporation rate Not applicable.

Information with regard to physical hazard

classes
Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void
Flammable liquids Void

(Contd. on page 6)



## according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.09.2024 Version number 4 (replaces version 3) Revision: 09.09.2024

Trade name: weber Cultural lime cement paint, cement

		(Contd. of page 5)
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

## **SECTION 10: Stability and reactivity**

- 10.1 Reactivity When mixed with water the product hardens forming a stable non-reactive mass.
- **10.2 Chemical stability** Stable at recommended storage conditions
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

- 10.5 Incompatible materials: Acids, ammonium salts, aluminum, non-precious metals.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compon	nents	1	Type	1	Value	1	Species
CAS: 65997-15-1 cement, portland, white							
Dermal LD50 >2,000 mg/kg (Rabbit)							
Copolymer of vinyl acetate and ethylene with mineral additives and protective colloids							
Oral	LD50	>2,000 mg	/kg (Rat)				

## Skin corrosion/irritation

Causes skin irritation.

## Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)



## according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.09.2024 Version number 4 (replaces version 3) Revision: 09.09.2024

Trade name: weber Cultural lime cement paint, cement

(Contd. of page 6)

#### 11.2 Information on other hazards

## **Endocrine disrupting properties**

None of the ingredients is listed.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test / Effective concentration / Method / Assessment

Copolymer of vinyl acetate and ethylene with mineral additives and protective colloids

LC50/96h >100 mg/l (Cyprinus Carpio (common carp))

**12.2 Persistence and degradability** The product is not biodegradable.

**12.3 Bioaccumulative potential** Does not accumulate in organisms

**12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment

**PBT:** Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

European	European waste catalogue					
17 01 01	17 01 01   concrete					
16 03 03*	P* inorganic wastes containing hazardous substances					
10 13 06	10 13 06 particulates and dust (except 10 13 12 and 10 13 13)					
HP4	HP4 Irritant - skin irritation and eye damage					
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity					

#### **Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

## **SECTION 14: Transport information**

14.1 UN number or ID number ADR, ADN, IMDG, IATA

Void

(Contd. on page 8)



## according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.09.2024 Version number 4 (replaces version 3) Revision: 09.09.2024

Trade name: weber Cultural lime cement paint, cement

	(Contd. of page
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordi IMO instruments	ng to Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Cement clinker is exempted from REACH registration (REACH Article 2(7)(b) and Annex V point 10)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

#### Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

## **REGULATION (EC) No 1907/2006 ANNEX XVII**

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII Entry no. 47 Chromium VI compounds)

Conditions of restriction: 47

## DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

### **REGULATION (EU) 2019/1148**

## Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

## **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

#### Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

(Contd. on page 9)





## according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.09.2024 Version number 4 (replaces version 3) Revision: 09.09.2024

Trade name: weber Cultural lime cement paint, cement

(Contd. of page 8)

## Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

## Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

## Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation

The classification of the mixture is generally based on the calculation method using substance data according Specific target organ toxicity (single exposure) to Regulation (EC) No 1272/2008.

## **Department issuing SDS:**

Saint-Gobain Finland Oy / Weber

**QEHS** 

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

#### Contact:

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 520

## Version number of previous version: 3

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

(Contd. on page 10)





# Safety Data Sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.09.2024 Version number 4 (replaces version 3) Revision: 09.09.2024

Trade name: weber Cultural lime cement paint, cement

(Contd. of page 9)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

FUC