

Revision: 15.12.2022



# Safety Data Sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024

Version number 4 (replaces version 3)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: weber 4100 Self Levelling

Safety data sheet no.: 358P0509

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Construction chemicals Filler and surfacer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

1.4 Emergency telephone number:

0800 147 111 (toll-free) 09 471 977 (standard rate)

Finnish Poison Information Centre

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

### 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms** 



GHS05

### Signal word Danger

### Hazard-determining components of labelling:

cement portland, grey

**Hazard statements** 

H315 Causes skin irritation.

H318 Causes serious eye damage.

### Precautionary statements

P102 Keep out of reach of children.

P261 Avoid breathing dust.

(Contd. on page 2)



### according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024 Version number 4 (replaces version 3) Revision: 15.12.2022

Trade name: weber 4100 Self Levelling

(Contd. of page 1)

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### 2.3 Other hazards

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

### Results of PBT and vPvB assessment

**PBT:** Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

**Description:** Ready-mixed mortar with Portland cement

Dangerous components:		
CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	50-75%
CAS: 1317-65-3 EINECS: 215-279-6 Reg.nr.: 01-2119486795-18-xxxx	calcium carbonate substance with a Community workplace exposure limit	10-25%
CAS: 7778-18-9 EINECS: 231-900-3 Reg.nr.: 01-2119444918-26-xxxx	calcium sulphate, natural substance with a Community workplace exposure limit	2-5%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey	2-5%

### **SVHC** Void

### **Additional information**

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**After inhalation** Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)





# according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024 Version number 4 (replaces version 3) Revision: 15.12.2022

Trade name: weber 4100 Self Levelling

(Contd. of page 2)

#### After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

### After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

Rinse opened eye forat least 15 minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

### After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

### 4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation.

Risk of eye damage in contact with dry or moist product.

May irritate moist skin in prolonged contact.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

### Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

The product is not combustible.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

### 5.3 Advice for firefighters

Protective equipment: No special measures required.

# **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Wear protective clothing.

**6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.

### 6.3 Methods and material for containment and cleaning up:

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)





# according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024 Version number 4 (replaces version 3) Revision: 15.12.2022

Trade name: weber 4100 Self Levelling

(Contd. of page 3)

# 7.2 Conditions for safe storage, including any incompatibilities Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Not required. Further information about storage conditions: Store in dry conditions.

7.3 Specific end use(s) No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

Finland: cement dust

**PNECs** 

LEP (Spain)

HTP(8h) = 5 mg/m3, inhalable dust HTP(8h) = 1 mg/m3, respirable dust

DNELs		
CAS: 131	7-65-3 calcium carbona	te
Oral	Derived No Effect Level	6.1 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	6.36 mg/m³ (worker local long term value)
		1.06 mg/m³ (consumer local long term value)
CAS: 6599	97-16-2 Cement, alumin	a, chemicals
Inhalative	Derived No Effect Level	2.5 mg/m³ (worker systemic long term value)
		5 mg/m³ (worker systemic short term value)
CAS: 7778	8-18-9 calcium sulphate	, natural
Oral	Derived No Effect Level	1.52 mg/kgxday (consumer systemic long term value)
		11.4 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	21.17 mg/m³ (worker systemic long term value)
		5,082 mg/m³ (worker systemic short term value)
		5.29 mg/m³ (consumer systemic long term value)
		3,811 mg/m³ (consumer systemic short term value)

CAS: 65997-16-2	Cement,	alumina.	chemicals

Predicted No-Effect Concentration | 260 mg/l (fresh water rating factor)

	<b>3</b> ,			
CAS No. / Designation of material / % / Type / Value / Unit				
CAS: 14808-60-7 Silicon	·			
	Long-term value: 0.1* mg/m³ *respirable fraction			
MAK (Germany)	alveolengängige Fraktion			
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m³			

Short-term value: 0.6\* 0.2\*\* mg/m³ Long-term value: 0.3\* 0.1\*\* mg/m³

\*total:,\*\*total, respirabel: K Long-term value: 0.05 mg/m³

\*Fracción resp:n,d,y

(Contd. on page 5)



# according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024 Version number 4 (replaces version 3) Revision: 15.12.2022

Trade name: weber 4100 Self Levelling

		(Contd. of page 4)
TWA (Italy)	Long-term value: 0.025 mg/m³ A2, (j)	
VLE (Portugal)	Long-term value: 0.025 mg/m³ Resp.;A2; fibrose pulmonar; cancro do pulmão	
OEL (Sweden)	Long-term value: 0.1 mg/m³ C, M, respirabel fraktion	
HTP (Finland)	Long-term value: 0.05 0.1* mg/m³ alveolijae;*sitovat raja-arvot, pöly	
CAS: 1317-65-3 calcium	carbonate	
TWA (Italy)	Long-term value: 10 mg/m³ (e)	
CAS: 7778-18-9 calcium	sulphate, natural	
MAK (Germany)	Long-term value: 4E** mg/m³ alveoleng.: Abschn.IIIb.*einatembar:Abschn.Vf)/g)	
LEP (Spain)	Long-term value: 10 mg/m³ e	
TWA (Italy)	Long-term value: 10 mg/m³ (i)	
VLE (Portugal)	Long-term value: 10 mg/m³ Fração inalável; Sintomas nasais	
CAS: 65997-15-1 cement	portland, grey	
AGW (Germany)	Long-term value: 5 E mg/m³ DFG	
LEP (Spain)	Long-term value: 4 mg/m³ fracción respirable: e, d	
TWA (Italy)	Long-term value: 1 mg/m³ (e, j), A4	
VLE (Portugal)	Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma	
HTP (Finland)	Long-term value: 5* 1** mg/m³ *hengittyvä pöly, **alveolijae	

### 8.2 Exposure controls

# Individual protection measures, such as personal protective equipment

# General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device. Filter P3.

### Hand protection

The hands must be cleaned from the powder before putting on the gloves.

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

(Contd. on page 6)





### according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024 Version number 4 (replaces version 3) Revision: 15.12.2022

Trade name: weber 4100 Self Levelling

(Contd. of page 5)

**Eye/face protection** Tightly sealed goggles **Body protection**: Protective work clothing.

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

**General Information** 

Colour: Grey

Odour: Specific type
Odour threshold: Not determined.

Boiling point or initial boiling point and boiling

range Undetermined.

**Flammability** Product is not flammable.

Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: Not applicable
Auto-ignition temperature: Not determined.
Decomposition temperature: Not determined.

pH at 20 °C <11

Viscosity:

**Kinematic viscosity dynamic:**Not determined.
Not determined.

Solubility

Water: Miscible

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure:

Not applicable.

Density and/or relative density

**Density at 20 °C:** 1.4-1.6 g/cm³ Not applicable.

Particle characteristics

See section 3.

**9.2 Other information**No further relevant information available.

Appearance:

Form: Powder

Important information on protection of health

and environment, and on safety.

**Explosive properties:** Product does not present an explosion hazard.

Minimum ignition energy

Solvent content:

Organic solvents: 0.0 % EU-VOC (%) 0.00 %

EU-VOC (g/L)

Solids content: 100 %

Change in condition Softening point/range

Oxidising properties Not determined.

(Contd. on page 7)



### according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024 Version number 4 (replaces version 3) Revision: 15.12.2022

Trade name: weber 4100 Self Levelling

		(Contd. of page
Evaporation rate	Not applicable.	
Information with regard to physical haz	zard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

Not reactive under normal conditions of use

In reaction with water the product will harden into a stable mass that is not reactive under normal conditions.

10.2 Chemical stability Stable at recommended storage conditions

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid

Avoid water ingress/moisture during storage (the product will react with moisture and harden). Humidity (during storage).

#### 10.5 Incompatible materials:

Acids, ammonium salts, aluminum, non-precious metals.

Acids, ammonium salts, aluminium powder.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Componen	ts	1	Type	1	Value	1	Species
CAS: 1317-	65-	3 calcium	carbonate				
Oral LD:	50	>2,000 mg/	/kg (Rat)				
Dermal LD:	50	>2,000 mg/	/kg (Rat)				

(Contd. on page 8)



# according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024 Version number 4 (replaces version 3) Revision: 15.12.2022

Trade name: weber 4100 Self Levelling

		(Cor	ntd. of page 7)
CAS: 6	5997-1	16-2 Cement, alumina, chemicals	
Oral	LD50	) >2,000 mg/kg (Rat)	
Dermal	LD50	>2,000 mg/kg (Rat)	
CAS: 77	778-18	8-9 calcium sulphate, natural	
Oral	LD50	) >2,000 mg/kg (Rat)	
CAS: 68	5997-1	15-1 cement portland, grey	
Dermal	LD50	) >2,000 mg/kg (Rabbit)	

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

### Endocrine disrupting properties

None of the ingredients is listed.

# **SECTION 12: Ecological information**

### 12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test	Type of test / Effective concentration / Method / Assessment		
CAS: 1317-6	5-3 calcium carbonate		
LC50/96h	>100 mg/l (Fish)		
EC50/48h	>100 mg/l (aquatic invertebrates)		
EC50/72h	>14 mg/l (aquatic algae and cyanobacteria)		
CAS: 65997-	16-2 Cement, alumina, chemicals		
LC50/96h	100 mg/l (Fish)		
EC50/24h	6.4 mg/l (aquatic invertebrates)		
EC50/48h	5.4 mg/l (aquatic invertebrates)		
EC50/72h	3.6 mg/l (aquatic algae and cyanobacteria)		
NOEC (72h)	2.6 mg/l (aquatic algae and cyanobacteria)		
NOEC (48h)	3.4 mg/l (aquatic invertebrates)		
CAS: 7778-1	8-9 calcium sulphate, natural		
LC50/48h	79-1,970 mg/l (aquatic invertebrates)		
LC50/96h	79-2,980 mg/l (Fish)		
EC50/72h	>79 mg/l (aquatic algae and cyanobacteria)		
12.2 Persiste	ence and degradability The product is not biodegradable.		

(Contd. on page 9)





# according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024 Version number 4 (replaces version 3) Revision: 15.12.2022

Trade name: weber 4100 Self Levelling

(Contd. of page 8)

Λ	Λ	et	h	O	d

### CAS: 1317-65-3 calcium carbonate

Biod. (28 days) >90 %

### 12.3 Bioaccumulative potential Does not accumulate in organisms

**12.4 Mobility in soil** No further relevant information available.

### 12.5 Results of PBT and vPvB assessment

**PBT:** Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

# 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

#### Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

### Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment	
CAS: 1317-65-3 calcium carbonate	
EC 50 (3h) >1,000 mg/l (microorganisms)	
CAS: 65997-16-2 Cement, alumina, chemicals	
EC 50 (3h) 1,000 mg/l (microorganisms)	
CAS: 7778-18-9 calcium sulphate, natural	
EC 50 (3h) >1,000 mg/l (microorganisms)	

### Additional ecological information:

### **General notes:**

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

### Waste disposal key:

The classification in a waste code according to the european waste catalogue (EWC) is to be made in accordance with the regional responsable for waste disposal

European	European waste catalogue			
17 01 01	concrete			
16 03 03*	inorganic wastes containing hazardous substances			
10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10			

### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 10)





### according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024 Version number 4 (replaces version 3) Revision: 15.12.2022

Trade name: weber 4100 Self Levelling

Recommended cleaning agent: Thoroughly shake out sacks.

(Contd. of page 9)

SECTION 14: Transport information	
14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordi IMO instruments	ng to Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Cement clinker is exempted from REACH registration (REACH Article 2(7)(b) and Annex V point 10)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

# Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

### **REGULATION (EC) No 1907/2006 ANNEX XVII**

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII Entry no. 47 Chromium VI compounds)

Conditions of restriction: 47

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

### **REGULATION (EU) 2019/1148**

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 11)





# according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024 Version number 4 (replaces version 3) Revision: 15.12.2022

Trade name: weber 4100 Self Levelling

(Contd. of page 10)

#### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

### Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

### Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008	
Skin corrosion/irritation	Expert judgement
Serious eye damage/irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### Department issuing SDS:

Saint-Gobain Finland Oy / Weber

**QEHS** 

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

#### Contact:

Tel. +358-(0)10-44 22 00 Fax +358-(0)10-44 22 520

Version number of previous version: 3

### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 12)



(Contd. of page 11)



# **Safety Data Sheet**

# according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.05.2024 Version number 4 (replaces version 3) Revision: 15.12.2022

Trade name: weber 4100 Self Levelling

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

### \* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

- EUG