




H: 130 mm D: 117 mm W: 195 mm



H: 110 mm D: 68 mm W: 69 mm

Standards

Facemask EN 140:1998
Cartridge filter
EN 14387:2004+A1:2008 A2P3 R D

Weight


Mask + Filters: S/M 288 g, M/L 295 g
Filters: 204 g

Shelf Life

5 years (mask & filters). See storage conditions on Instructions for Use. Filters are re-usable and changeable.

Efficiency

P3 >99,95% for 0,3 µ particulate
At 5000 ppm:
> 35 minutes Cyclohexane (C₆H₁₂)



Patent Pending

1. Particulate pleated filter (total length 645 mm)
2. Activated carbon treated for gas adsorption
3. Designed to help airflow diffusion and full usage of the activated carbon
4. Inhalation valve



Material

- Inner mask body in Medical Grade TPE
- Covers in PP/ABS
- Valve body in nylon with silicone diaphragms
- Gas filters: Activated carbon sealed into ABS shell

- Particulate filters: Mechanical type multi-layer HESPA synthetic media encapsulated with TPE. Particulate filters are integrated with the carbon element



Comes with **life extender** protective caps

Part #	Description
SPR213L (S/M) SPR223L (M/L)	Elipse® A2P3 Respirator Package also includes: ■ Replaceable filters
FIL253L	Elipse® A2P3 Replacement Cartridges Pair
SPM009	Elipse® Carry Case
SPM646	Elipse® Fit Test Adaptor

Applications

Welding & Grinding: metal fumes and dust in confined spaces (gas welding)

Constructions: paint, moulds

Manufacturing: solvents, various organic gases

Automotive & Marine: coal dust, silica dust

Agriculture: pesticides