

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 4 (replaces version 3)

Revision: 13.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **weber PTM Fast cement filler**

Safety data sheet no.: 358P0546

UFI: ME54-KKSQ-YD96-VW55

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Construction chemicals

Filler and surfacer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Finland Oy / Weber

PL 70

(Strömberginkuja 2)

FIN-00381 Helsinki

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 295

DL-productsafety.fi@saint-gobain.com

www.fi.weber

1.4 Emergency telephone number:

0800 147 111 (toll-free)

09 471 977 (standard rate)

Finnish Poison Information Centre

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Results of in vitro- tests have shown that cement based mixtures with more than 1% of cement cause serious skin irritation and serious eye damage, therefore the classification of these mixtures regarding H315 and H318 is not based on the calculation of the ingredients or the pH in this case.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05

Signal word Danger

Hazard-determining components of labelling:

Cement, alumina, chemicals

cement portland, grey

(Contd. on page 2)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 4 (replaces version 3)

Revision: 13.03.2023

Trade name weber PTM Fast cement filler

(Contd. of page 1)

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements

P102 Keep out of reach of children.

P261 Avoid breathing dust.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description: Ready-mixed mortar with Portland cement

Dangerous components:

CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	25-50%
CAS: 471-34-1 EINECS: 207-439-9 Reg.nr.: 01-2119486795-18-xxxx	calcium carbonate substance with a Community workplace exposure limit	25-50%
CAS: 65997-16-2 EINECS: 266-045-5	Cement, alumina, chemicals ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315	10-20%
CAS: 7778-18-9 EINECS: 231-900-3 Reg.nr.: 01-2119444918-26-xxxx	calcium sulphate, natural substance with a Community workplace exposure limit	5-10%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	2-5%

SVHC Void

Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 4 (replaces version 3)

Revision: 13.03.2023

Trade name weber PTM Fast cement filler

(Contd. of page 2)

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8). For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact Immediately wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

The product is not combustible.

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Wear protective clothing.

6.2 Environmental precautions: No special measures required.

6.3 Methods and material for containment and cleaning up:

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

Dispose of contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

EUG

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 4 (replaces version 3)

Revision: 13.03.2023

Trade name weber PTM Fast cement filler

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Store in dry conditions.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs		
CAS: 471-34-1 calcium carbonate		
Inhalative	Derived No Effect Level	6.36 mg/m ³ (worker local long term value) 1.06 mg/m ³ (consumer local long term value)
CAS: 65997-16-2 Cement, alumina, chemicals		
Inhalative	Derived No Effect Level	2.5 mg/m ³ (worker systemic long term value) 5 mg/m ³ (worker systemic short term value)
CAS: 7778-18-9 calcium sulphate, natural		
Oral	Derived No Effect Level	1.52 mg/kgxday (consumer systemic long term value) 11.4 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	21.17 mg/m ³ (worker systemic long term value) 5,082 mg/m ³ (worker systemic short term value) 5.29 mg/m ³ (consumer systemic long term value) 3,811 mg/m ³ (consumer systemic short term value)
CAS No. / Designation of material / % / Type / Value / Unit		
CAS: 14808-60-7 Silicon dioxide (Quartz sand)		
BOELV (European Union)		Long-term value: 0.1* mg/m ³ *respirable fraction
MAK (Germany)		Long-term value: 0.05 mg/m ³ alveolengängige Fraktion
GV (Denmark)		Short-term value: 0.6* 0.2** mg/m ³ Long-term value: 0.3* 0.1** mg/m ³ *total, **total, respirabel, EK
LEP (Spain)		Long-term value: 0.05 mg/m ³ *Fracción resp:n,d,y

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 4 (replaces version 3)

Revision: 13.03.2023

Trade name weber PTM Fast cement filler

(Contd. of page 4)

TWA (Italy)	Long-term value: 0.025 mg/m ³ A2, (j)
VLE (Portugal)	Long-term value: 0.05 mg/m ³ Resp.;A2; fibrose pulmonar; cancro do pulmão
OEL (Sweden)	Long-term value: 0.1 mg/m ³ C, M, respirabel fraktion
HTP (Finland)	Long-term value: 0.05 0.1* mg/m ³ alveolijae;*sitovat raja-arvot, pöly
CAS: 471-34-1 calcium carbonate	
LEP (Spain)	Long-term value: 10 mg/m ³
TWA (Italy)	Long-term value: (10) mg/m ³ (e)
VLE (Portugal)	Long-term value: (10) mg/m ³ (Irritação)
CAS: 7778-18-9 calcium sulphate, natural	
AGW (Germany)	Long-term value: 6 A mg/m ³ DFG
LEP (Spain)	Long-term value: 10 mg/m ³ e
TWA (Italy)	Long-term value: 10 mg/m ³ (i)
VLE (Portugal)	Long-term value: 10 mg/m ³ Fração inalável; Sintomas nasais
CAS: 65997-15-1 cement portland, grey	
AGW (Germany)	Long-term value: 5 E mg/m ³ DFG
LEP (Spain)	Long-term value: 4 mg/m ³ fracción respirable: e, d
TWA (Italy)	Long-term value: 1 mg/m ³ (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m ³ Fração resp.;A4,função pulm.,sintomas resp.,asma
HTP (Finland)	Long-term value: 5* 1** mg/m ³ *hengittyvä pöly, **alveolijae

8.2 Exposure controls

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Filter P3.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 4 (replaces version 3)

Revision: 13.03.2023

Trade name weber PTM Fast cement filler

(Contd. of page 5)

Hand protection

Protective gloves.

The hands must be cleaned from the powder before putting on the gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Eye/face protection Tightly sealed goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour: According to product specification

Odour: Specific type

Odour threshold: Not determined.

Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling range Undetermined.

Flammability Product is not flammable.

Lower and upper explosion limit

Lower: Not determined.

Upper: Not determined.

Flash point: Not applicable

Ignition temperature: Not determined.

Decomposition temperature: Not determined.

pH 12-13

Viscosity:

Kinematic viscosity Not applicable.

dynamic: Not applicable.

Solubility

Water: Miscible

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure: Not applicable.

Density and/or relative density

Density: Not applicable.

Relative density Not determined.

Vapour density Not applicable.

Particle characteristics See item 3.

9.2 Other information

No further relevant information available.

Appearance:

Form: Powder

Important information on protection of health and environment, and on safety.

Auto-ignition temperature: Product is not self-igniting.

Explosive properties: Product does not present an explosion hazard.

EU-VOC (g/L)

Solids content: 100.0 %

Change in condition

Softening point/range

Oxidising properties Not determined.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 4 (replaces version 3)

Revision: 13.03.2023

Trade name weber PTM Fast cement filler

(Contd. of page 6)

Evaporation rate	Not applicable.
-------------------------	-----------------

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity When mixed with water the product hardens forming a stable non-reactive mass.

10.2 Chemical stability Stable at recommended storage conditions

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

10.5 Incompatible materials: Acids, ammonium salts, aluminum, non-precious metals.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	/	Type	/	Value	/	Species
CAS: 471-34-1 calcium carbonate						
Oral	LD50			6,450 mg/kg		(Rat)
Dermal	LD50			6,450 mg/kg		(Rat)
CAS: 65997-16-2 Cement, alumina, chemicals						
Oral	LD50			>2,000 mg/kg		(Rat)
Dermal	LD50			>2,000 mg/kg		(Rat)

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 4 (replaces version 3)

Revision: 13.03.2023

Trade name weber PTM Fast cement filler

(Contd. of page 7)

CAS: 7778-18-9 calcium sulphate, natural

Oral LD50 >2,000 mg/kg (Rat)

CAS: 65997-15-1 cement portland, grey

Dermal LD50 >2,000 mg/kg (Rabbit)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test / Effective concentration / Method / Assessment

CAS: 471-34-1 calcium carbonate

EC50/72h 14 mg/l (Algae)

CAS: 65997-16-2 Cement, alumina, chemicals

LC50/96h 100 mg/l (Fish)

EC50/48h 5.4 mg/l (Daphnia magna)

EC50/72h 3.6 mg/l (Algae)

CAS: 7778-18-9 calcium sulphate, natural

LC50/48h 79-1,970 mg/l (Daphnia magna)

LC50/96h >79 mg/l (Oryzias latipes (Japanese medaka))

79-2,980 mg/l (Fish)

EC50/72h >79 mg/l (Selenastrum capricornutum (Green algae))

12.2 Persistence and degradability The product is not biodegradable.

12.3 Bioaccumulative potential Does not accumulate in organisms

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 9)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 4 (replaces version 3)

Revision: 13.03.2023

Trade name weber PTM Fast cement filler

(Contd. of page 8)

12.7 Other adverse effects

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment	
CAS: 65997-16-2 Cement, alumina, chemicals	
EC 50 (3h)	1,000 mg/l (Activated sludge)
CAS: 7778-18-9 calcium sulphate, natural	
EC 50 (3h)	>1,000 mg/l (Activated sludge)

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

Waste disposal key:

The classification in a waste code according to the european waste catalogue (EWC) is to be made in accordance with the regional responsible for waste disposal

European waste catalogue	
17 01 01	concrete
16 03 03*	inorganic wastes containing hazardous substances
10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10
HP4	Irritant - skin irritation and eye damage

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Thoroughly shake out sacks.

SECTION 14: Transport information

14.1 UN number or ID number ADR, IMDG, IATA	Void
14.2 UN proper shipping name ADR, IMDG, IATA	Void
14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Void

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 4 (replaces version 3)

Revision: 13.03.2023

Trade name weber PTM Fast cement filler

(Contd. of page 9)

14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds)

Conditions of restriction: 47

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2023

Version number 4 (replaces version 3)

Revision: 13.03.2023

Trade name weber PTM Fast cement filler

(Contd. of page 10)

Relevant phrases

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

Department issuing SDS:

Saint-Gobain Finland Oy / Weber

QEHS

P.O.Box 70 (Strömberginkuja 2)

FI-00381 Helsinki

Contact:

Tel. +358-(0)10-44 22 00

Fax +358-(0)10-44 22 520

Version number of previous version: 3**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.